

AD 580 Robust De-humidification



78 Ltrs / Day extraction capacity
recommended upto 8500 cu.ft



Made in Germany
since 1990



Blue Dry Technology
most energy efficient dehumidification @ 1400 watts



Easy-To-Use Electronic eDRY
displays RH level, kWh and operating hours



Optimum Dehumidifying Performance
high air flow at 820 m³ / hr



Dependable & Durable
modular metal body



AD 580

origin

AERIAL
Made in Germany

Specifications

Recommended Coverage (Indicative)*	cu.ft	8500
Extraction (30 °C/80% RH)	1/24 hr	78 l / 24 hr
De-humidifying performance/ power consumption at**		
30°C/80% RH	1/24 h	78 l / 1400 watt
20°C/60% RH	1/24 h	52 l / 1200 watt
10°C/70% RH	1/24 h	35 l / 1010 watt
Max. power consumption	Watt	1400
Air circulation rate	m³/h	Speed 1/2 = 600 / 886 m³/h
Working temperature range	°C	+3° C to +32° C
Noise Level	dB	55
Power supply	V/Hz	230V/50Hz
Dimension (height/width/depth)	Inches	32" x 19" X 20"
Weight	Kg	55
Arrangement		On the ground
Coolant		R410a
Condensate drainage		Water tank (16l) or tube connector
Maintenance required		Empty container, check and change filters
Timer (Optional)		Yes

* Guideline figures/based on experience **Based on DIN EN 810
• Subject to technical changes • Made in Germany



EDRY
DRYING CONTROL



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense

Climatronics
Environment, Controlled.