

AD 750 Heavy Duty Mobile De-humidifier



55 Ltrs / Day
extraction capacity



Recommended Upto 6000 cu.ft
indicative coverage area



Made in Germany
since 1990



Blue Dry Technology
most energy efficient dehumidification @ 900 watts



Optimum Dehumidifying Performance
high air flow at 710 m³/hr



New Casing Technology
with recyclable PE, UV stabilized



AD 750

Specifications

Recommended Coverage (Indicative)*	cu.ft	6000
Extraction (30 °C/80% RH)	1/24 hr	55.0 l / 24 hr
De-humidifying performance/ power consumption at**		
30°C/80% RH	1/24 h	55.0 l / 900 watt
20°C/60% RH	1/24 h	24.5 l / 660 watt
10°C/70% RH	1/24 h	14.0 l / 560 watt
Max. power consumption	Watt	900
Air circulation rate	m³/h	710
Working temperature range	°C	+3° C to +32° C
Noise Level	dB	53
Power supply	V/Hz	230V/50Hz
Dimension (height/width/depth)	Inches	35" x 20" X 19"
Weight	Kg	42
Arrangement	On the ground, two large casters, various handles	
Coolant	R407c	
Condensate drainage	Water tank (12l) or tube connector	
Maintenance required	Empty container, check and change filters	
Timer (Optional)	Yes	

* Guideline figures/based on experience **Based on DIN EN 810
 • Subject to technical changes • Made in Germany



Industries

Healthcare Pharma R & D Hotel Warehousing Printing Food Museum & Art Galleries Defense