

O¹³⁰ robust dehumidifier



130 ltrs/day
extraction capacity



Recommended up to 14,000 cu.ft. | 397 cu.mt.
indicative coverage area



Anti-corrosive body
roto molded housing for robust handling



Led Display and Electronic Control
precise operation



Water Pump
dispenses condensate up to 15 feet



Quick Defrost
hot-gas bypass



Higher Air Flow @ 850 m³/hr
for consistent and low levels of RH



O130

Specifications

| | | |
|---|----------------|------------------|
| Extraction (l/24hr) (30°C, 80% RH) | l/24 hr | 130 |
| Recommended Coverage (Indicative)(Industry) | cu.ft. cu.mt | Upto 14000 397 |
| Dimensions | inches | 22 x 23 x 38 |
| Rated Power, Power Supply 220V-240V/50Hz | watts | 1190 |
| Rated Current | | 5.3A |
| Air Flow | m³/hr | 850 |
| Refrigerant | | R410A |
| Compressor | | Rotary |
| Noise Level (approx.) | dB | 60 |
| Weight | kgs | 65 |
| Running Temperature | | 5°C - 35°C |

origin



Ductable Option
air outlet can be ducted for focused drying



Big Wheels and Big Metal Handle
to ensure optimum on-site mobility



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense